

Rectangle 160 LED Recessed Downlight



INTERIOR CEILING RECESSED




INTERIOR CEILING RECESSED




GVREC-10.5W-160


10.5W
 503lm 3000K
 CRI>90
 LED
 EXCL.700mA 15V DRIVER



LED(CREE) ADJUSTABLE CUT-OFF ANGLE 38°



145*78mm
 5~25mm



NW:0.78kg
 GW:11.9kg






COLOR TEMPERATURE

2700K ●
 3000K ●
 4000K ●
 5000K ○
 6500K ●

FINISH

○ AW
 ● AS
 ● OJ



ACCESSORIES

REQUIREMENTS

AD0845 (KEGU)
 Un:AC 220~240V
 Uout:DC 15V
 Iout:700mA

AD0799 (KEGU)
AD0861 (EUCHIPS)
 Un:AC 220~240V
 Uout:DC 15V
 Iout:700mA

AD0888 (EUCHIPS)
 Un:AC 220~240V
 Uout:DC 15V
 Iout:700mA

AD0850 (OSRAM)
 Un:AC 220~240V
 Uout:DC 15V
 Iout:700mA



ACCESSORIES

REQUIREMENTS

AD0845 (KEGU)
 Un:AC 220~240V
 Uout:DC 15V
 Iout:700mA

AD0799 (KEGU)
AD0861 (EUCHIPS)
 Un:AC 220~240V
 Uout:DC 15V
 Iout:700mA


AD0888 (EUCHIPS)
 Un:AC 220~240V
 Uout:DC 15V
 Iout:700mA

AD0850 (OSRAM)
 Un:AC 220~240V
 Uout:DC 15V
 Iout:700mA






GVREC-21W-160


2*10.5W
 1006lm 3000K
 CRI>90
 LED
 EXCL. 2*700mA 15V DRIVER



LED(CREE) ADJUSTABLE CUT-OFF ANGLE 38°



145*130mm
 5~25mm



NW:1.20kg
 GW:16.9kg



COLOR TEMPERATURE

2700K ●
 3000K ●
 4000K ●
 5000K ○
 6500K ●

FINISH

○ AW
 ● AS
 ● OJ