

Dolux 78

Surface Mounted LED Downlight

Model: GVDOL-12W-78

Product Description

LED spotlight for indoor, with adjustable head.
Available in Matt Black and Matt White finish.



Outer Dimensions



Specification

Light source

Light source: Citizen COB
Output (W): 350mA 31V 10.85W
Total energy consumption (W): 12.76W
Color temperature: 2700K/3000K/4000K
CRI: 90
Photobiological hazard:RG1
Real Lumen: 780
Lm/Real W: 61
Lifetime: 50.000h
MacAdam steps: 3
UGR: <11

GEAR

This product incl:
HEP G5R15W350LRP power supply(on/off).

Phase cut/DALI/0-10V drivers are available upon request.

Warranty

3 Years for residential
5 years for commercial

Luminaire

IP54 for indoor use
Crossing: No

Finish

Black/White

Material

Aluminum

Light Distribution

3000K 18°

h(m)	E(lx)	Ø(m)
1	4400	Ø0.32
2	1100	Ø0.64
3	488.9	Ø0.96
4	275.0	Ø1.29
5	176.0	Ø1.61

3000K 28°

h(m)	E(lx)	Ø(m)
1	2761	Ø0.52
2	690.2	Ø1.03
3	306.8	Ø1.55
4	172.6	Ø2.07
5	110.4	Ø2.58

3000K 39°

h(m)	E(lx)	Ø(m)
1	1797	Ø0.71
2	449.2	Ø1.42
3	199.7	Ø2.12
4	112.3	Ø2.84
5	71.88	Ø3.55