



Sirius Series

Recessed COB LED Downlight



Features

- No UV or IR rays. No mercury
- Dimmable and Non-Dimmable option available
- Superb dimming effect
- COB LED chips with high luminous flux
- Aluminum profile provides excellent thermal dissipation
- Short heatsink designed for any ceiling installations


- IP44 Rated
- 5 Years Warranty
- It is designed for general lighting applications in office, supermarket, shop, school, hotel, etc. It is also widely used for public areas, such as stairway, lobby, reception, corridors etc.


Specifications


CCT Colour	2700K/3000K/4000K/5000K		
Power Consumption	10-45W		
Lumen	100lm/w		
Input Voltage	AC 100-240V		
Beam Angle	24°/36°/45°/60°		


CRI	>80/>90 Options				
Power Factor	>0.9				
Chipset	Citizen COB				
Dimmable	Triac, 0-10V or Dali Options				

Dimensions & Photometrics



































Sirius Series

Recessed COB LED Downlight

Models

Model	LED Chip	Wattage	Beam Angle	сст	Lumens(±5%)	Dimension	Cutout
GUSIR-10-3	_	10W	60°		640-800lm	Ø110*53mm	Ø90-100mm
GUSIR-13-3		13W	60°		900-1100lm	Ø110*53mm	Ø90-100mm
GUSIR-18-4		18W	24°/45°/60°		1835-2070lm	Ø145*65mm	Ø120-130mm
GUSIR-25-4		25W	24°/45°/60°		2250-2750lm	Ø145*65mm	Ø120-130mm
GUSIR-18-6	Citizen COB 25W 35W	36°/60°	2700K 3000K	1850-2160lm	Ø190*75mm	Ø160-170mm	
GUSIR-25-6		36°/60°		2350-2875lm	Ø190*75mm	Ø160-170mm	
GUSIR-35-6		35W	36°/60°	4000K 5000K	3290-3885lm	Ø190*75mm	Ø160-170mm
GUSIR-45-6		45W	36°/60°		3870-4770lm	Ø190*75mm	Ø160-170mm
GUSIR-18-8		18W	24°/36°/60°		1850-2160lm	Ø225*75mm	Ø200-210mm
GUSIR-25-8	25W 35W	24°/36°/60°	_	2350-2875lm	Ø225*75mm	Ø200-210mm	
GUSIR-35-8		24°/36°/60°		3360-3955lm	Ø225*75mm	Ø200-210mm	
GUSIR-45-8		45W	24°/36°/60°		3870-4770lm	Ø225*75mm	Ø200-210mm



ADC12
ALUMINUM PROFILE
provides excellent thermal dissipation. Short heatsink designed for any ceiling installations



