

Jupiter Mini Series 02

LED Recessed Down Light

*Architectural
Lighting*

- Architectural Design
- Narrow Trim
- SDCM <2/<3
- Anti-glare, High CRI 90 & 95 options
- IP20/IP44/IP54/IP65 options
- LM80: 60000 hrs
- Triac / 0-10V / Dali Dimmable options
- High quality OSRAM SMD Chipset
- High light output
- High quality Aluminum housing
- Applications include shopping centres, walkways, hotels, restaurants, galleries, display cases & household

Specifications

Colour Range 2700K / 3000K / 4000K / 5000K

Lumen Efficiency (lm) 70lm/w

Power Consumption 2W / 4W / 10W / 20W / 30W

Input Voltage 200V/240V AC

Dimensions (mm)	Cutout		
	2W	45*45*49	37*37
	4W	75*45*49	68*37
	10W	147*45*49	140*37
	20W	280*45*49	273*37
	30W	413*45*49	405*37

CRI >90 / 95

Power Factor >0.95

Chipset OSRAM SMD

Driver Class II

Dimmable Triac / 0-10V / Dali (options)

Housing Material Aluminum Alloy + Clear Diffuser

Housing Colour White / Grey / Black



Greenlux

5/216 Blackshaws Rd,
Altona North VIC 3025 Australia

Phone: 1300 650 625
Email: enquiries@greenlux.com.au

Facebook: [greenluxlighting](https://www.facebook.com/greenluxlighting)
Twitter: [GreenluxLED](https://twitter.com/GreenluxLED)

IES

LM80
-B10

RCM

SAA

TUV

CE

5 Yrs
Warranty

MacAdams
Rating 2/3


Jupiter Mini Series 02

LED Recessed Down Light

*Architectural
Lighting*




GJJUM-2W-02




Power: 2W (700mA/3V)
Lamp: OSRAM SMD (CRI>90/95)
AC: 200-240V

Beam Angle	Model	Lumen	Finish	LED Colour	LED Driver
45°	GJJUM-2W-02	120lm	1 Matt White 2 Matt Black 3 Silver	1 3000K 2 4000K 3 5000K 4 2700K	1 On and off 2 Trac dimmable 3 1-10V dimmable 4 Dal 5 Bluetooth

LED Driver
LED Colour
Finish




GJJUM-20W-02




Power: 20W (600mA/30V)
Lamp: OSRAM SMD (CRI>90/95)
AC: 200-240V

Beam Angle	Model	Lumen	Finish	LED Colour	LED Driver
45°	GJJUM-20W-02	1370lm	1 Matt White 2 Matt Black 3 Silver	1 3000K 2 4000K 3 5000K 4 2700K	1 On and off 2 Trac dimmable 3 1-10V dimmable 4 Dal 5 Bluetooth

LED Driver
LED Colour
Finish




GJJUM-4W-02




Power: 4W (600mA/6V)
Lamp: OSRAM SMD (CRI>90/95)
AC: 200-240V

Beam Angle	Model	Lumen	Finish	LED Colour	LED Driver
45°	GJJUM-4W-02	210lm	1 Matt White 2 Matt Black 3 Silver	1 3000K 2 4000K 3 5000K 4 2700K	1 On and off 2 Trac dimmable 3 1-10V dimmable 4 Dal 5 Bluetooth

LED Driver
LED Colour
Finish




GJJUM-30W-02




Power: 30W (600mA/45V)
Lamp: OSRAM SMD (CRI>90/95)
AC: 200-240V

Beam Angle	Model	Lumen	Finish	LED Colour	LED Driver
45°	GJJUM-30W-02	1000lm	1 Matt White 2 Matt Black 3 Silver	1 3000K 2 4000K 3 5000K 4 2700K	1 On and off 2 Trac dimmable 3 1-10V dimmable 4 Dal 5 Bluetooth

LED Driver
LED Colour
Finish



GJJUM-10W-02



Power: 10W (600mA/15V)
Lamp: OSRAM SMD (CRI>90/95)
AC: 200-240V

Beam Angle	Model	Lumen	Finish	LED Colour	LED Driver
45°	GJJUM-10W-02	650lm	1 Matt White 2 Matt Black 3 Silver	1 3000K 2 4000K 3 5000K 4 2700K	1 On and off 2 Trac dimmable 3 1-10V dimmable 4 Dal 5 Bluetooth

LED Driver
LED Colour
Finish

