

Latte Fixed

LED Recessed Down Light

*Architectural
Lighting*

- Architectural Design
- Narrow Trim
- SDCM <2/<3
- Anti-glare, High CRI 90 & 95 options
- IP44/IP54/IP65 options
- LM80: 60000 hrs
- Triac / 0-10V / Dali Dimmable options
- High quality COB Chipset
- High light output
- High quality Aluminum housing
- Applications include shopping centres, walkways, hotels, restaurants, galleries, display cases & household

Specifications

Colour Range	2700K / 3000K / 4000K / 5000K	
Lumen Efficiency (lm)	130lm/w	
Power Consumption	6W / 9W / 12W / 16W / 20W	
Input Voltage	200V/240V AC	
Dimensions (mm)	6W	350mA / 16V
	9W	240mA / 36V
	12W	260mA / 36V
	16W	350mA / 36V
	20W	500mA / 36V
CRI	>90 / 95	
Power Factor	>0.95	
Chipset	Citizen COB	
Driver	Class II	
Dimmable	Triac / 0-10V / Dali (options)	
Housing Material	Aluminum Alloy + Clear Diffuser	
Housing Colour	White/Silver/Chrome/Black	



Greenlux

5/216 Blackshaws Rd,
Altona North VIC 3025 Australia

Phone: 1300 650 625
Email: enquiries@greenlux.com.au

Facebook: [greenluxlighting](https://www.facebook.com/greenluxlighting)
Twitter: [GreenluxLED](https://twitter.com/GreenluxLED)

IES

LM80
-B10

RCM

SAA

TUV

CE

5 Yrs
Warranty

MacAdams
Rating 2/3

Latte Fixed

LED Recessed Down Light

*Architectural
Lighting*


CCT 2700-5000K



80mm




80mm



92mm



92mm



105mm

Model Number	CCT	LED Type	Lumen(lm)	Dimension (mm)	Cutout Size (mm)	Beam Angle	Voltage(V)
GDLAT-6W-F	2700K 3000K 4000K 5000K	Citizen COB	780	Ø85*70	80	24° / 45° / 60°	AC200-240V
GDLAT-9W-F			1170	Ø85*90	80		
GDLAT-12W-F			1560	Ø98*74	92		
GDLAT-16W-F			2080	Ø98*90	92		
GDLAT-20W-F			2600	Ø120*95	105		

