

# Mini Star Pinhole LED Recessed Downlight



## Features

1. Equipped with original packaging, this product uses a high-efficiency, energy-saving, and environmentally friendly imported COB LED light source that delivers excellent color rendering. It enhances product quality, creates a comfortable and ambient lighting environment, and has a service life of up to 50,000 hours.
2. Featuring a unique optical design and a high-transmission cover, it ensures accurate light distribution, high brightness, and low glare, providing natural, soft, and uniform lighting.
3. Constructed from high-quality die-cast aluminum alloy and designed with optimal aerodynamics, it guarantees superior heat dissipation performance.
4. The design integrates a minimalist aesthetic, resulting in a compact and elegant form.
5. Available in a range of power options to suit different lighting needs and spaces.
6. Ideal for residential applications.

## Application

Home, office, shops, etc.



50000hrs



Dimmable



Various sizes



Various CCT




RCM



5 Years Warranty




GDMIN-3.5W-4232-60




Power: 3.5W (300mA/9V)  
Lamp: EPISTAR COB (CRI>80, CRI>90)  
AC: 200-240V

Beam Angle	Model	Lumen	Finish	LED Colour	LED Driver
60°	GDMIN-3.5W-4232-60	300lm	<input type="checkbox"/> 1 Matt White <input checked="" type="checkbox"/> 2 Matt Black <input type="checkbox"/> 3 Silver	<input type="checkbox"/> 1 3000K <input checked="" type="checkbox"/> 2 4000K <input type="checkbox"/> 3 5000K <input type="checkbox"/> 4 2700K	<input type="checkbox"/> 1 On and off <input checked="" type="checkbox"/> 2 Triac dimmable




GDMIN-3.5W-5231-60




Power: 3.5W (300mA/9V)  
Lamp: EPISTAR COB (CRI>80, CRI>90)  
AC: 200-240V

Beam Angle	Model	Lumen	Finish	LED Colour	LED Driver
60°	GDMIN-3.5W-5231-60	300lm	<input type="checkbox"/> 1 Matt White <input checked="" type="checkbox"/> 2 Matt Black <input type="checkbox"/> 3 Silver	<input type="checkbox"/> 1 3000K <input checked="" type="checkbox"/> 2 4000K <input type="checkbox"/> 3 5000K <input type="checkbox"/> 4 2700K	<input type="checkbox"/> 1 On and off <input checked="" type="checkbox"/> 2 Triac dimmable




GDMIN-3.5W-6042-60



Power: 3.5W (300mA/9V)  
Lamp: EPISTAR COB (CRI>80, CRI>90)  
AC: 200-240V


Beam Angle	Model	Lumen	Finish	LED Colour	LED Driver
60°	GDMIN-3.5W-6042-60	300lm	<input type="checkbox"/> 1 Matt White <input checked="" type="checkbox"/> 2 Matt Black <input type="checkbox"/> 3 Silver	<input type="checkbox"/> 1 3000K <input checked="" type="checkbox"/> 2 4000K <input type="checkbox"/> 3 5000K <input type="checkbox"/> 4 2700K	<input type="checkbox"/> 1 On and off <input checked="" type="checkbox"/> 2 Triac dimmable



# Mini Star Pinhole LED Recessed Downlight




GDMIN-3W-4640




Power: 3W (650mA/3.1V)  
Lamp: EP/STAR COB (CRI>80, CRI>90)  
AC: 200-240V

Beam Angle	Model	Lumen	Finish	LED Colour	LED Driver
30°	GDMIN-3W-4640-30	180lm	1 Matt White 2 Matt Black 3 Silver	1 3000K 2 4000K 3 5000K 4 2700K	1 On and off 2 Triac dimmable
60°	GDMIN-3W-4640-60	180lm			
120°	GDMIN-3W-4640-120	180lm			




GDMIN-3W-6040





Power: 3W (650mA/3.1V)  
Lamp: EP/STAR COB (CRI>80, CRI>90)  
AC: 200-240V

Beam Angle	Model	Lumen	Finish	LED Colour	LED Driver
30°	GDMIN-3W-6040-30	180lm	1 Matt White 2 Matt Black 3 Silver	1 3000K 2 4000K 3 5000K 4 2700K	1 On and off 2 Triac dimmable
60°	GDMIN-3W-6040-60	180lm			
120°	GDMIN-3W-6040-120	180lm			



GDMIN-3W-5027-30



Power: 3W (650mA/3.1V)  
Lamp: EP/STAR COB (CRI>80, CRI>90)  
AC: 200-240V

Beam Angle	Model	Lumen	Finish	LED Colour	LED Driver
30°	GDMIN-3W-5027-30	180lm	1 Matt White 2 Matt Black 3 Silver	1 3000K 2 4000K 3 5000K 4 2700K	1 On and off 2 Triac dimmable

