



greenlux
cost reduction LED lighting

Tempest Linear Series LED Batten Fixture

Available in Common, Sensor, Emergency, Sensor & Emergency



Replaceable LED strips
Easy Maintenance

- Available in Common, Sensor, Emergency and Emergency/Sensor
- Low-profile, light weight
- Excellent heat dissipation and superior lighting effect
- Replaceable LED strips with press terminal block for easy maintenance
- 6mm wiring block
- Non-breakable and non-discolor PC lens
- Ceiling, wall mounted or suspended installation
- High light output 1000 ~ 13500lm
- High quality LED Chipset SMD 2835
- Non-discoloring opal polycarbonate diffuser for soft and even light output
- IP20 Rated
- 5 Years Warranty
- Applications include stairwells, parking areas, schools, corridors, storage rooms etc.

Dimensions

Product Dimensions (mm)	(LxWxH)	
	2Ft	613*111*78
	4Ft	1223*111*78
	5Ft	1511*111*78
Housing Materials		Cold Rolled Steel Housing + Aluminum Heatsink
Lens		PC Diffuser
Housing Colour		White

RCM

SAA

IES

TUV

CE

RoHS

LM80

IP 20



greenlux
cost reduction LED lighting

Tempest Linear Series LED Batten Fixture



Specifications

Colour Range	3000-6000k
Power Consumption	10W ~ 120W
Lumens	1000 ~ 13500lm
Chipset	Epistar SMD 2835
Input Voltage	100-277V AC
Beam angle	110°
Ra	>83/90
PF	>0.95
Dimmer	On/Off, 0-10V, Dali (option)
Sensor	Microwave Motion (option)
Emergency	90 minutes (option)
Mounting Height	8m Max.
Driver	Class II SAA

Microwave Sensor

Sensor Range	16m * 8m (D * H) Max.
Sensing Interval	5s to 5min max (adjustable)
Sensing interval output	10% light output at standby (adjustable)
Detection Angle	150° Wall Installation 360° Ceiling Installation

Emergency

Type	Maintained
Battery (High Temp)	9.6V 3.2AH Ni-MH Rechargeable
Emergency Output	30% nominal power
Emergency Duration	>90 Minutes
Charge Time	<12 Hours





greenlux
cost reduction LED lighting

Tempest Linear Series LED Batten Fixture

Model	CCT	lumen(lm) (± 10%)	Power(W) (± 10%)	LED type	Dimming (option)	Dimensions (MM)
GOTEP-10W-LI2F-CW	5000	1200	10	SMD	On/Off Dali 0-10V	613 * 111 * 78
GOTEP-10W-LI2F-NW	4000	1100				
GOTEP-10W-LI2F-WW	3000	1000				
GOTEP-20W-LI4F-CW	5000	2200	20	SMD		1223 * 111 * 78
GOTEP-20W-LI4F-NW	4000	2100				
GOTEP-20W-LI4F-WW	3000	2000				
GOTEP-40W-LI4F-CW	5000	4400	40	SMD		1223 * 111 * 78
GOTEP-40W-LI4F-NW	4000	4200				
GOTEP-40W-LI4F-WW	3000	4000				
GOTEP-60W-LI4F-CW	5000	6600	60	SMD		1223 * 111 * 78
GOTEP-60W-LI4F-NW	4000	6300				
GOTEP-60W-LI4F-WW	3000	6000				
GOTEP-80W-LI4F-CW	5000	9600	80	SMD		1223 * 111 * 78
GOTEP-80W-LI4F-NW	4000	9200				
GOTEP-80W-LI4F-WW	3000	8800				
GOTEP-90W-LI4F-CW	5000	10800	90	SMD		1225 * 111 * 78
GOTEP-90W-LI4F-NW	4000	10300				
GOTEP-90W-LI4F-WW	3000	9900				
GOTEP-50W-LI5F-CW	5000	5500	50	SMD		1511 * 111 * 78
GOTEP-50W-LI5F-NW	4000	5250				
GOTEP-50W-LI5F-WW	3000	5000				
GOTEP-60W-LI5F-CW	5000	6600	60	SMD		1511 * 111 * 78
GOTEP-60W-LI5F-NW	4000	6300				
GOTEP-60W-LI5F-WW	3000	6000				
GOTEP-100W-LI5F-CW	5000	12000	100	SMD		1511 * 111 * 78
GOTEP-100W-LI5F-NW	4000	10500				
GOTEP-100W-LI5F-WW	3000	11000				
GOTEP-120W-LI5F-CW	5000	14400	120	SMD		1511 * 111 * 78
GOTEP-120W-LI5F-NW	4000	13800				
GOTEP-120W-LI5F-WW	3000	13200				